




Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
0.74	0.10	1.02 +/- 0.08	-001	0.029	0.004	0.040 +/- 0.003
1.07	0.10	1.27 +/- 0.08	-002	0.042	0.004	0.050 +/- 0.003
4.70	0.13	1.42 +/- 0.08	-901	0.185	0.005	0.056 +/- 0.003
1.42	0.10	1.53 +/- 0.08	-003	0.056	0.004	0.060 +/- 0.003
6.07	0.13	1.63 +/- 0.08	-902	0.239	0.005	0.064 +/- 0.003
7.65	0.13		-903	0.301	0.005	
1.78	0.13		-004	0.070	0.005	0.070 +/- 0.003
2.57	0.13	1.78 +/- 0.08	-005	0.101	0.005	
2.90	0.13		-006	0.114	0.005	
3.69	0.13		-007	0.145	0.005	
4.47	0.13		-008	0.176	0.005	
5.28	0.13		-009	0.208	0.005	
6.07	0.13		-010	0.239	0.005	
7.66	0.13		-011	0.302	0.005	
9.25	0.13		-012	0.364	0.005	
10.82	0.13		-013	0.426	0.005	
12.42	0.13		-014	0.489	0.005	
14.00	0.18		-015	0.551	0.007	
15.60	0.23		-016	0.614	0.009	
17.16	0.23		-017	0.676	0.009	
18.77	0.23		-018	0.739	0.009	
20.35	0.23		-019	0.801	0.009	
21.95	0.23		-020	0.864	0.009	
23.52	0.23		-021	0.926	0.009	
25.12	0.25		-022	0.989	0.010	
26.70	0.25		-023	1.051	0.010	
28.30	0.25		-024	1.114	0.010	
29.87	0.28		-025	1.176	0.011	
31.47	0.28		-026	1.239	0.011	
33.05	0.28		-027	1.301	0.011	
34.65	0.33		-028	1.364	0.013	
37.82	0.33		-029	1.489	0.013	
41.00	0.33		-030	1.614	0.013	
44.17	0.38		-031	1.739	0.015	
47.37	0.38		-032	1.865	0.015	
50.52	0.46		-033	1.989	0.018	
53.67	0.46		-034	2.113	0.018	
56.87	0.46		-035	2.239	0.018	
60.04	0.46		-036	2.364	0.018	
63.22	0.46		-037	2.489	0.018	
66.40	0.51		-038	2.614	0.020	
69.57	0.51		-039	2.739	0.020	
72.76	0.51		-040	2.865	0.020	
75.92	0.61		-041	2.989	0.024	
82.27	0.61		-042	3.239	0.024	
88.62	0.61		-043	3.489	0.024	
94.97	0.69		-044	3.739	0.027	
101.32	0.69		-045	3.989	0.027	
107.67	0.76		-046	4.239	0.030	
114.02	0.76		-047	4.489	0.030	
120.37	0.76		-048	4.739	0.030	
126.72	0.94		-049	4.989	0.037	
133.07	0.94		-050	5.239	0.037	
8.92	0.13	1.83 +/- 0.08	-904	0.351	0.005	0.072 +/- 0.003
10.52	0.13		-905	0.414	0.005	




Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
11.89	0.13	1.98 +/- 0.08	-906	0.468	0.005	0.078 +/- 0.003
13.46	0.18	2.08 +/- 0.08	-907	0.530	0.007	0.082 +/- 0.003
16.36	0.23	2.21 +/- 0.08	-908	0.644	0.009	0.087 +/- 0.003
17.93	0.23	2.46 +/- 0.08	-909	0.706	0.009	0.097 +/- 0.003
19.18	0.23		-910	0.755	0.009	
1.24	0.10		-102	0.049	0.004	0.103 +/- 0.003
2.06	0.13	2.62 +/- 0.08	-103	0.081	0.005	
2.84	0.13		-104	0.112	0.005	
3.63	0.13		-105	0.143	0.005	
4.42	0.13		-106	0.174	0.005	
5.23	0.13		-107	0.206	0.005	
6.02	0.13		-108	0.237	0.005	
7.59	0.13		-109	0.299	0.005	
9.19	0.13		-110	0.362	0.005	
10.77	0.13		-111	0.424	0.005	
12.37	0.13		-112	0.487	0.005	
13.94	0.18		-113	0.549	0.007	
15.54	0.23		-114	0.612	0.009	
17.12	0.23		-115	0.674	0.009	
18.72	0.23		-116	0.737	0.009	
20.29	0.25		-117	0.799	0.010	
21.89	0.25		-118	0.862	0.010	
23.47	0.25		-119	0.924	0.010	
25.07	0.25		-120	0.987	0.010	
26.64	0.25		-121	1.049	0.010	
28.24	0.25		-122	1.112	0.010	
29.82	0.30		-123	1.174	0.012	
31.42	0.30		-124	1.237	0.012	
32.99	0.30		-125	1.299	0.012	
34.59	0.30		-126	1.362	0.012	
36.17	0.30		-127	1.424	0.012	
37.77	0.30		-128	1.487	0.012	
39.34	0.38		-129	1.549	0.015	
40.94	0.38		-130	1.612	0.015	
42.52	0.38		-131	1.674	0.015	
44.12	0.38		-132	1.737	0.015	
45.69	0.38		-133	1.799	0.015	
47.29	0.43		-134	1.862	0.017	
48.90	0.43		-135	1.925	0.017	
50.47	0.43		-136	1.987	0.017	
52.07	0.43		-137	2.050	0.017	
53.64	0.43		-138	2.112	0.017	
55.25	0.43		-139	2.175	0.017	
56.82	0.43		-140	2.237	0.017	
58.42	0.51		-141	2.300	0.020	
59.99	0.51		-142	2.362	0.020	
61.60	0.51		-143	2.425	0.020	
63.17	0.51		-144	2.487	0.020	
64.77	0.51		-145	2.550	0.020	
66.34	0.51		-146	2.612	0.020	
67.95	0.56		-147	2.675	0.022	
69.52	0.56		-148	2.737	0.022	
71.12	0.56		-149	2.800	0.022	
72.69	0.56		-150	2.862	0.022	
75.87	0.61		-151	2.987	0.024	
82.22	0.61		-152	3.237	0.024	
88.57	0.61		-153	3.487	0.024	




Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
94.92	0.71	2.62 +/- 0.08	-154	3.737	0.028	0.103 +/- 0.003
101.27	0.71		-155	3.987	0.028	
107.62	0.76		-156	4.237	0.030	
113.97	0.76		-157	4.487	0.030	
120.32	0.76		-158	4.737	0.030	
126.67	0.89		-159	4.987	0.035	
133.02	0.89		-160	5.237	0.035	
139.37	0.89		-161	5.487	0.035	
145.72	0.89		-162	5.737	0.035	
152.07	0.89		-163	5.987	0.035	
158.42	1.02		-164	6.237	0.040	
164.77	1.02		-165	6.487	0.040	
171.12	1.02		-166	6.737	0.040	
177.47	1.02		-167	6.987	0.040	
183.82	1.14		-168	7.237	0.045	
190.17	1.14		-169	7.487	0.045	
196.52	1.14		-170	7.737	0.045	
202.87	1.14		-171	7.987	0.045	
209.22	1.27		-172	8.237	0.050	
215.57	1.27		-173	8.487	0.050	
221.92	1.27	2.95 +/- 0.10	-174	8.737	0.050	0.116 +/- 0.004
228.27	1.27		-175	8.987	0.050	
234.62	1.40		-176	9.237	0.055	
240.97	1.40		-177	9.487	0.055	
247.32	1.40		-178	9.737	0.055	
21.92	0.23	3.00 +/- 0.10	-911	0.863	0.009	0.118 +/- 0.004
23.47	0.23		-912	0.924	0.009	
25.04	0.25		-913	0.986	0.010	
26.59	0.25		-914	1.047	0.010	
29.74	0.25		-916	1.171	0.010	
34.42	0.30	3.53 +/- 0.10	-918	1.355	0.012	0.139 +/- 0.004
37.47	0.36		-920	1.475	0.014	
43.69	0.36		-924	1.720	0.014	
53.09	0.46		-928	2.090	0.018	
59.36	0.46		-932	2.337	0.018	
4.34	0.13		-201	0.171	0.005	
5.94	0.13		-202	0.234	0.005	
7.52	0.13		-203	0.296	0.005	
9.12	0.13		-204	0.359	0.005	
10.69	0.13		-205	0.421	0.005	
12.29	0.13		-206	0.484	0.005	
13.87	0.18		-207	0.546	0.007	
15.47	0.23		-208	0.609	0.009	
17.04	0.23		-209	0.671	0.009	
18.64	0.25		-210	0.734	0.010	
20.22	0.25		-211	0.796	0.010	
21.82	0.25		-212	0.859	0.010	
23.39	0.25		-213	0.921	0.010	
24.99	0.25		-214	0.984	0.010	
26.57	0.25		-215	1.046	0.010	
28.17	0.30		-216	1.109	0.012	
29.74	0.30		-217	1.171	0.012	
31.34	0.30		-218	1.234	0.012	
32.92	0.30		-219	1.296	0.012	
34.52	0.30		-220	1.359	0.012	
36.09	0.30		-221	1.421	0.012	
37.69	0.38		-222	1.484	0.015	
40.87	0.38		-223	1.609	0.015	
44.04	0.38		-224	1.734	0.015	
47.22	0.46		-225	1.859	0.018	
50.39	0.46		-226	1.984	0.018	



Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
53.57	0.46	3.53 +/- 0.10	-227	2.109	0.018	0.139 +/- 0.004
56.74	0.51		-228	2.234	0.020	
59.92	0.51		-229	2.359	0.020	
63.09	0.51		-230	2.484	0.020	
66.27	0.51		-231	2.609	0.020	
69.44	0.61		-232	2.734	0.024	
72.62	0.61		-233	2.859	0.024	
75.79	0.61		-234	2.984	0.024	
78.97	0.61		-235	3.109	0.024	
82.14	0.61		-236	3.234	0.024	
85.32	0.61		-237	3.359	0.024	
88.49	0.61		-238	3.484	0.024	
91.67	0.71		-239	3.609	0.028	
94.84	0.71		-240	3.734	0.028	
98.02	0.71		-241	3.859	0.028	
101.19	0.71		-242	3.984	0.028	
104.37	0.71		-243	4.109	0.028	
107.54	0.76		-244	4.234	0.030	
110.72	0.76		-245	4.359	0.030	
113.89	0.76		-246	4.484	0.030	
117.07	0.76		-247	4.609	0.030	
120.24	0.76		-248	4.734	0.030	
123.42	0.89		-249	4.859	0.035	
126.59	0.89		-250	4.984	0.035	
129.77	0.89		-251	5.109	0.035	
132.94	0.89		-252	5.234	0.035	
136.12	0.89		-253	5.359	0.035	
139.29	0.89		-254	5.484	0.035	
142.47	0.89		-255	5.609	0.035	
145.64	0.89		-256	5.734	0.035	
148.82	0.89		-257	5.859	0.035	
151.99	0.89		-258	5.984	0.035	
158.34	1.02		-259	6.234	0.040	
164.69	1.02		-260	6.484	0.040	
171.04	1.02		-261	6.734	0.040	
177.39	1.02		-262	6.984	0.040	
183.74	1.14		-263	7.234	0.045	
190.09	1.14		-264	7.484	0.045	
196.44	1.14		-265	7.734	0.045	
202.79	1.14		-266	7.984	0.045	
209.14	1.27		-267	8.234	0.050	
215.49	1.27		-268	8.484	0.050	
221.84	1.27		-269	8.734	0.050	
228.19	1.27		-270	8.984	0.050	
234.54	1.40		-271	9.234	0.055	
240.89	1.40		-272	9.484	0.055	
247.24	1.40		-273	9.734	0.055	
253.59	1.40		-274	9.984	0.055	
266.29	1.40		-275	10.484	0.055	
278.99	1.65		-276	10.984	0.065	
291.69	1.65		-277	11.484	0.065	
304.39	1.65		-278	11.984	0.065	
329.79	1.65		-279	12.984	0.065	
355.19	1.65		-280	13.984	0.065	
380.57	1.65		-281	14.983	0.065	
405.26	1.91		-282	15.955	0.075	
430.66	2.03		-283	16.955	0.080	
456.06	2.16		-284	17.955	0.085	
10.46	0.13	5.33 +/- 0.13	-309	0.412	0.005	0.210 +/- 0.005
12.07	0.13		-310	0.475	0.005	
13.64	0.18		-311	0.537	0.007	




Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
15.24	0.23	5.33 +/- 0.13	-312	0.600	0.009	0.210 +/- 0.005
16.81	0.23		-313	0.662	0.009	
18.42	0.25		-314	0.725	0.010	
19.99	0.25		-315	0.787	0.010	
21.59	0.25		-316	0.850	0.010	
23.16	0.25		-317	0.912	0.010	
24.77	0.25		-318	0.975	0.010	
26.34	0.25		-319	1.037	0.010	
27.94	0.30		-320	1.100	0.012	
29.51	0.30		-321	1.162	0.012	
31.12	0.30		-322	1.225	0.012	
32.69	0.30		-323	1.287	0.012	
34.29	0.30		-324	1.350	0.012	
37.47	0.38		-325	1.475	0.015	
40.64	0.38		-326	1.600	0.015	
43.82	0.38		-327	1.725	0.015	
46.99	0.38		-328	1.850	0.015	
50.17	0.46		-329	1.975	0.018	
53.34	0.46		-330	2.100	0.018	
56.52	0.46		-331	2.225	0.018	
59.69	0.46		-332	2.350	0.018	
62.87	0.51		-333	2.475	0.020	
66.04	0.51		-334	2.600	0.020	
69.22	0.51		-335	2.725	0.020	
72.39	0.51		-336	2.850	0.020	
75.57	0.61		-337	2.975	0.024	
78.74	0.61		-338	3.100	0.024	
81.92	0.61		-339	3.225	0.024	
85.09	0.61		-340	3.350	0.024	
88.27	0.61		-341	3.475	0.024	
91.44	0.71		-342	3.600	0.028	
94.62	0.71		-343	3.725	0.028	
97.79	0.71		-344	3.850	0.028	
100.97	0.71		-345	3.975	0.028	
104.14	0.71		-346	4.100	0.028	
107.32	0.76		-347	4.225	0.030	
110.49	0.76		-348	4.350	0.030	
113.67	0.76		-349	4.475	0.030	
116.84	0.76		-350	4.600	0.030	
120.02	0.76		-351	4.725	0.030	
123.19	0.76		-352	4.850	0.030	
126.37	0.94		-353	4.975	0.037	
129.54	0.94		-354	5.100	0.037	
132.72	0.94		-355	5.225	0.037	
135.89	0.94		-356	5.350	0.037	
139.07	0.94		-357	5.475	0.037	
142.24	0.94		-358	5.600	0.037	
145.42	0.94		-359	5.725	0.037	
148.59	0.94		-360	5.850	0.037	
151.77	0.94		-361	5.975	0.037	
158.12	1.02		-362	6.225	0.040	
164.47	1.02		-363	6.475	0.040	
170.82	1.02		-364	6.725	0.040	
177.17	1.02		-365	6.975	0.040	
183.52	1.14		-366	7.225	0.045	
189.87	1.14		-367	7.475	0.045	
196.22	1.14		-368	7.725	0.045	
202.57	1.14		-369	7.975	0.045	
208.92	1.27		-370	8.225	0.050	
215.27	1.27		-371	8.475	0.050	
221.62	1.27		-372	8.725	0.050	



Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
227.97	1.27	5.33 +/- 0.13	-373	8.975	0.050	0.210 +/- 0.005
234.32	1.40		-374	9.225	0.055	
240.67	1.40		-375	9.475	0.055	
247.02	1.40		-376	9.725	0.055	
253.37	1.40		-377	9.975	0.055	
266.07	1.52		-378	10.475	0.060	
278.77	1.52		-379	10.975	0.060	
291.47	1.65		-380	11.475	0.065	
304.17	1.65		-381	11.975	0.065	
329.57	1.65		-382	12.975	0.065	
354.97	1.78		-383	13.975	0.070	
380.37	1.78		-384	14.975	0.070	
405.26	1.91		-385	15.955	0.075	
430.66	2.03		-386	16.955	0.080	
456.06	2.16		-387	17.955	0.085	
481.46	2.29		-388	18.955	0.090	
506.86	2.41		-389	19.955	0.095	
532.26	2.41		-390	20.955	0.095	
557.66	2.54		-391	21.955	0.100	
582.68	2.67		-392	22.940	0.105	
608.08	2.79		-393	23.940	0.110	
633.48	2.92		-394	24.940	0.115	
658.88	3.05		-395	25.940	0.120	
113.67	0.84	6.99 +/- 0.15	-425	4.475	0.033	0.275 +/- 0.006
116.84	0.84		-426	4.600	0.033	
120.02	0.84		-427	4.725	0.033	
123.20	0.84		-428	4.850	0.033	
126.37	0.94		-429	4.975	0.037	
129.54	0.94		-430	5.100	0.037	
132.72	0.94		-431	5.225	0.037	
135.90	0.94		-432	5.350	0.037	
139.07	0.94		-433	5.475	0.037	
142.24	0.94		-434	5.600	0.037	
145.42	0.94		-435	5.725	0.037	
148.60	0.94		-436	5.850	0.037	
151.77	0.94		-437	5.975	0.037	
158.12	1.02		-438	6.225	0.040	
164.47	1.02		-439	6.475	0.040	
170.82	1.02		-440	6.725	0.040	
177.17	1.02		-441	6.975	0.040	
183.52	1.14		-442	7.225	0.045	
189.87	1.14		-443	7.475	0.045	
196.22	1.14		-444	7.725	0.045	
202.57	1.14		-445	7.975	0.045	
215.27	1.40		-446	8.475	0.055	
227.97	1.40		-447	8.975	0.055	
240.67	1.40		-448	9.475	0.055	
253.57	1.40		-449	9.983	0.055	
266.07	1.52		-450	10.475	0.060	
278.77	1.52		-451	10.975	0.060	
291.47	1.52		-452	11.475	0.060	
304.17	1.52		-453	11.975	0.060	
316.87	1.52		-454	12.475	0.060	
329.57	1.52		-455	12.975	0.060	
342.27	1.78		-456	13.475	0.070	
354.97	1.78		-457	13.975	0.070	
367.67	1.78		-458	14.475	0.070	
380.37	1.78		-459	14.975	0.070	
393.07	1.78		-460	15.475	0.070	
405.26	1.91		-461	15.955	0.075	
417.96	1.91		-462	16.455	0.075	

AS 568 O-ring Sizes



Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
430.66	2.03	6.99 +/- 0.15	-463	16.955	0.080	0.275 +/- 0.006
443.36	2.16		-464	17.455	0.085	
456.06	2.16		-465	17.955	0.085	
468.76	2.16		-466	18.455	0.085	
481.46	2.29		-467	18.955	0.090	
494.16	2.29		-468	19.455	0.090	
506.86	2.41		-469	19.955	0.095	
532.26	2.41		-470	20.955	0.095	
557.66	2.54		-471	21.955	0.100	
582.68	2.67		-472	22.940	0.105	
608.08	2.79		-473	23.940	0.110	
633.48	2.92		-474	24.940	0.115	
658.88	3.05		-475	25.940	0.120	

PPE does not accept responsibility for the accuracy of the data provided in this document.