


Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
1.15	0.13	1.00 +/- 0.08	R000	0.045	0.005	0.039 +/- 0.003
2.20	0.13	1.60 +/- 0.08	R00	0.087	0.005	0.063 +/- 0.003
2.40	0.13	1.90 +/- 0.08	R0	0.094	0.005	0.075 +/- 0.003
2.60	0.13		R1	0.102	0.005	
3.40	0.14		R2	0.134	0.006	
4.20	0.15		R3	0.165	0.006	
4.90	0.15		R4	0.193	0.006	
5.70	0.16		R5	0.224	0.006	
7.20	0.17		R6	0.283	0.007	
8.90	0.18	2.70 +/- 0.09	R7	0.350	0.007	0.106 +/- 0.004
8.90	0.18		R8	0.350	0.007	
10.50	0.19		R9	0.413	0.007	
12.10	0.21		R10	0.476	0.008	
13.60	0.22		R11	0.535	0.009	
15.10	0.23		R12	0.594	0.009	
16.90	0.24		R13	0.665	0.009	
18.40	0.25	3.60 +/- 0.10	R14	0.724	0.010	0.142 +/- 0.004
18.30	0.25		R15	0.720	0.010	
19.80	0.26		R16	0.780	0.010	
21.30	0.28		R17	0.839	0.011	
23.00	0.29		R18	0.906	0.011	
24.60	0.30		R19	0.969	0.012	
26.20	0.31		R20	1.031	0.012	
27.80	0.32		R21	1.094	0.013	
29.30	0.34		R22	1.154	0.013	
30.80	0.35		R23	1.213	0.014	
32.50	0.36	5.33 +/- 0.13	R24	1.280	0.014	0.210 +/- 0.005
34.10	0.37		R25	1.343	0.015	
35.60	0.39		R26	1.402	0.015	
37.30	0.39		R27	1.469	0.015	
37.47	0.38		R28	1.475	0.015	
40.64	0.38		R29	1.600	0.015	
43.82	0.38		R30	1.725	0.015	
46.99	0.38		R31	1.850	0.015	
50.17	0.46		R32	1.975	0.018	
53.34	0.46		R33	2.100	0.018	
56.52	0.46		R34	2.225	0.018	
59.69	0.46		R35	2.350	0.018	
62.87	0.51		R36	2.475	0.020	
66.04	0.51		R37	2.600	0.020	
69.22	0.51		R38	2.725	0.020	
72.39	0.51		R39	2.850	0.020	
75.57	0.61		R40	2.975	0.024	
78.74	0.61		R41	3.100	0.024	
81.92	0.61		R42	3.225	0.024	
85.09	0.61		R43	3.350	0.024	
88.27	0.61		R44	3.475	0.024	
91.44	0.71		R45	3.600	0.028	
94.62	0.71		R46	3.725	0.028	
97.79	0.71		R47	3.850	0.028	
100.97	0.71		R48	3.975	0.028	
104.14	0.71		R49	4.100	0.028	
107.32	0.76		R50	4.225	0.030	
110.49	0.76		R51	4.350	0.030	
113.67	0.76		R52	4.475	0.030	

LJF 'R' O-ring Sizes



Millimetres			Size Ref	Inches		
Internal Diameter (mm)	Internal Diameter Tolerance +/-	Cross Section (mm)		Internal Diameter (inches)	Internal Diameter Tolerance +/-	Cross Section (inches)
113.67	0.84	6.99 +/- 0.15	R53	4.475	0.033	0.275 +/- 0.006
116.84	0.84		R54	4.600	0.033	
120.02	0.84		R55	4.725	0.033	
123.20	0.84		R56	4.850	0.033	
126.37	0.94		R57	4.975	0.037	
129.54	0.94		R58	5.100	0.037	
132.72	0.94		R59	5.225	0.037	
135.90	0.94		R60	5.350	0.037	
139.07	0.94		R61	5.475	0.037	
142.24	0.94		R62	5.600	0.037	
145.42	0.94		R63	5.725	0.037	
148.60	0.94		R64	5.850	0.037	
151.77	0.94		R65	5.975	0.037	
158.12	1.02		R66	6.225	0.040	
164.47	1.02		R67	6.475	0.040	
170.82	1.02		R68	6.725	0.040	
177.17	1.02		R69	6.975	0.040	
183.52	1.14		R70	7.225	0.045	
189.87	1.14		R71	7.475	0.045	
196.22	1.14		R72	7.725	0.045	
202.57	1.14		R73	7.975	0.045	
215.27	1.40		R74	8.475	0.055	
227.97	1.40		R75	8.975	0.055	
240.67	1.40		R76	9.475	0.055	
253.57	1.40		R77	9.983	0.055	
266.07	1.52		R78	10.475	0.060	
278.77	1.52		R79	10.975	0.060	
291.47	1.52		R80	11.475	0.060	
304.17	1.52		R81	11.975	0.060	
316.87	1.52		R82	12.475	0.060	
329.57	1.52		R83	12.975	0.060	
342.27	1.78		R84	13.475	0.070	
354.97	1.78		R85	13.975	0.070	
367.67	1.78		R86	14.475	0.070	
380.37	1.78		R87	14.975	0.070	
393.07	1.78		R88	15.475	0.070	

PPE does not accept responsibility for the accuracy of the data provided in this document.